



SOUND CONTROL WITHOUT THE HEIGHT.

Maxxon® Commercial Acousti-Top® is the low-profile, high-performance sound control underlayment for new construction and renovation projects.

- Code-level sound control without the added height
- Ideal for concrete construction and multifamily renovation
- Compatible with virtually all LVT/ LVP, sheet vinyl, laminate, wood, tile and carpet
- Fast and easy installation for glue down or floating methods
- Point load resistance prevents damage

WHERE TO USE

Application

Single-family, multifamily, wood frame and light commercial construction.

Subfloor

Interior new or existing gypsum underlayments or concrete slabs.

MINIMUM:

50

I I C

LOW PROFILE. HIGH PERFORMANCE.

A lightweight mat, Maxxon Commercial Acousti-Top achieves high IIC ratings without impacting floor height. At only 45 pounds per roll, coverage per pound is three times greater than industry-standard rubber or cork mats.

Compatible with virtually all floor goods and adhesives, you can install Acousti-Top directly onto concrete or gypsum subfloor using glued down or floating methods.

PRODUCT INFORMATION

Thickness	3/16 in.: (1.6 mm)
Color	Dark gray
Underlayment Depth	Dependent on application
Installation Method	Dependent on application
Roll Width	42.5 in. (108 cm)
Roll Length	200 ft (61 m)
Coverage per Roll	708 ft ² (65.8 m ²)
Sound Control	Minimum 50 IIC



INSTALLATION & LIMITATIONS

See technical data sheet available at maxxon.com for limitations and complete installation instructions.

PACKAGING

45 lbs (20.4 kg)

FIRE RATINGS

Underwriters Laboratory International UL ER #8477-01. See technical data sheet for complete UL and fire assembly information.

PRO TIP

Acousti-Top is part of the Maxxon EZ Renovation System—designed to add sound control to multifamily construction renovation projects.



Maxxon Corporation
920 Hamel Road PO Box 253
Hamel, Minnesota 55340
800-238-8461
maxxon.com
info@maxxon.com

@Maxxon.Corporation
 maxxon-corporation