



## THE ROCK-SOLID SOLUTION FOR UNEVEN FLOORS.

Maxxon® Commercial Pro Level-Right® is a self-leveling, hydraulic cement-based underlayment designed to flatten and smooth concrete slabs.

- High compressive strengths — ideal for commercial, retail and institutional projects
- Suitable for small repair jobs to large projects
- No special subfloor prep, old floor removal or hand finishing required
- Cost-effective solution installed by approved applicators
- Batch mixed on site to meet project needs
- Cap existing floor goods and adhesive residue
- GREENGUARD Gold Certified

**BENEATH IT ALL, MAXXON DELIVERS.™**

### WHERE TO USE

#### *Application*

Commercial renovation and concrete construction.

#### *Subfloor*

Interior wood, concrete, terrazzo, ceramic, quarry, marble tile, old vinyl tile and radiant heat floors.

TYPICAL RANGE:  
**5,000-7,000**  
**PSI**

## SELF-LEVELING. FAST INSTALL.

Maxxon Commercial Pro Level-Right is the affordable, time-saving choice for resurfacing concrete slabs. Self-leveling to ¼ inch, the robust formulation can be applied from featheredge to 3 inch depths to correct uneven subfloors, yielding a smooth, level surface suitable for virtually any floor covering.

Batch mixed on site, it installs fast — covering up to 40,000 square feet per day — and can be walked on 2 to 4 hours after set. Ceramic tile can be installed within 2 to 4 hours after set and other floor goods can be installed after a successful moisture test.

## PRODUCT INFORMATION

<b>Compressive Strength</b> (Modified ASTM C109)	Typical range of 5,000–7,000 psi (34.5–48.3 MPa)
<b>Installation Depths</b>	From featheredge to 3 in. (0–76 mm) For deeper pours, contact Maxxon
<b>Dry Density</b>	115–125 lbs/ft <sup>3</sup> (1842–2002 kg/m <sup>3</sup> )
<b>Fire Performance</b> (ASTM E84)	Flame spread: 0 Fuel contribution: 0 Smoke development: 0

## INSTALLATION & LIMITATIONS

See technical data sheet available at [maxxon.com](http://maxxon.com) for limitations and complete installation instructions.

## PACKAGING

80 lbs (36 kg)

## FIRE RATINGS

Underwriters Laboratory International UL ER #8477-01. See technical data sheet for complete UL and fire assembly information.

## LEED INFORMATION

For information regarding how Maxxon Commercial Pro Level-Right may earn points toward LEED project certification, contact us at 800-356-7887 or visit [www.maxxon.com/go\\_green](http://www.maxxon.com/go_green).

## PRO TIP

May be used as part of a wear surface system — contact Maxxon for details.



## Maxxon Corporation

920 Hamel Road PO Box 253  
Hamel, Minnesota 55340  
800-356-7887

[maxxon.com](http://maxxon.com)

[info@maxxon.com](mailto:info@maxxon.com)

@Maxxon.Corporation

maxxon-corporation