

Gypsum Overspray

PRIMER

PRODUCT DESCRIPTION

Maxxon® Commercial Gypsum Overspray is used as a primer over Maxxon Underlayments before the installation of glue down finished floor goods*.

*Where floor goods manufacturers require special adhesive or installation systems, their requirements supersede these recommendations.

FEATURES & BENEFITS

- Enhances adhesive bond by reducing porosity factor to maintain proper adhesive open time
- Low odor, Low VOC

PRODUCT INFORMATION

Property	Liquid
VOC	0.02 g/L
Shelf Life	1 Year Unopened
Packaging	1-gallon (3.8 L) 5-gallon (18.9 L) 55-gallon (208.2 L) 265-gallon (1,003 L)
Coverage per undiluted gallon	300 ft ² (27.9 m ²)
Coverage per diluted gallon	6:1 Mix Ratio: 2,100 ft ² (195.1 m ²)



Gypsum Overspray

PRIMER

INSTALLATION

Surface Preparation

Before priming, test the underlayment for dryness. The underlayment must be fully dry before priming. Make sure substrate surface is broom cleaned, contaminant free and should have a smooth finish free from voids and sharp protrusions.

Tools

- Mixing bucket
- Measuring tool
- 1/4" nap roller or spray tool

Mix Ratio

Dilute material 6 parts water to 1 part concentrate.

Application

Roll or spray Maxxon Gypsum Overspray onto the floor at a rate of 300 ft² (27.9 m²) per gallon of mix.

For best results, Gypsum Overspray is applied about 1–2 hours prior to adhesive application.

STORAGE AND DISPOSAL

Keep from freezing; do not store below 40 °F (5 °C). Keep container closed when not in use. Keep in a dry, cool place.

Dispose of waste by following federal, state and local regulations. If spill occurs, clean up with potable water.

WARRANTY AND TECH SERVICES

Contact Maxxon before your project for complete warranty information. Technical performance verification and service is available through Maxxon Corporation or Maxxon Regional Representative throughout North America.



Maxxon Corporation
920 Hamel Road PO Box 253
Hamel, Minnesota 55340
800-238-8461
maxxon.com
info@maxxon.com

 @Maxxon.Corporation
 maxxon-corporation

JOB NAME: _____

DATE: _____

APPLICATOR: _____

Maxxon Corporation assumes no responsibility or liability for any errors or omissions in the content of this document. The information contained is subject to change without notice. Follow local and state regulations and use appropriate safety precautions and measures when installing Maxxon products. See related product literature at Maxxon.com or contact Maxxon Corporation for more information prior to installation.

©2024 Maxxon Corporation. All Rights Reserved. Maxxon and associated logos are registered trademarks of Maxxon Corporation, Hamel, MN, USA. Other trademarks, registered trademarks, product names or logos displayed are the property of their respective owners.