



THE TIME-SAVING SELF-LEVELER.

Hydraulic cement-based Maxxon® Commercial Level EZ™ is a low-prep, self-leveling underlayment — ideal for smoothing and capping gypsum and concrete subfloors.

- Minimal subfloor prep — clean, prime and pour
- Highly flowable, self-leveling at ¼ inch
- Ready for foot traffic in as little as 2 hours
- Install from featheredge to 2 inches (0 mm to 51 mm)
- Suitable for virtually all floor coverings

WHERE TO USE

Application

Multifamily wood frame, light commercial wood frame commercial, concrete construction and renovation.

Subfloor

Interior gypsum, concrete, wood.

MINIMUM:
5,000
PSI

REMARKABLY SMOOTH WITH A LEVEL THAT LASTS.

When resurfacing gypsum and concrete, go with the high-performance option that saves you time. Maxxon Commercial Level EZ requires no shotblasting. Simply clean, prime and pour.

The dimensionally stable, smooth-flowing formula can be applied from featheredge to 2 inch depths. It's ready to be walked on in 2–4 hours and is suitable for virtually any floor covering from carpet and LVT to ceramic tile. Maxxon Commercial Level EZ produces an exceptionally smooth, durable and flat surface that won't buckle, heave or curl.

PRODUCT INFORMATION

Compressive Strength (Modified ASTM C109)	24 hrs.: 2,000 psi (13.8 MPa) 7 days: 2,700 psi (18.6 MPa) 28 days: Minimum 5,000 psi (34.5 MPa)
Installation Depths	Featheredge–2 in. (0–51 mm) For deeper pours, contact Maxxon
Flexural Strength (ASTM C348)	1,000 psi (6.9 MPa) when dry
Dry Density	115–125 lbs/ft³ (1,842–2,002 kg/m³)
Working Time	15–20 min.
Coverage (per 50 lb bag)	Approximately 24 ft² at 1/4"*
Fire Performance (ASTM E84)	Flame spread: 0 Fuel contribution: 0 Smoke development: 0

* Depending on water demand used and slab condition.



INSTALLATION & LIMITATIONS

See technical data sheet available at Maxxon.com for limitations and complete installation instructions.

PACKAGING

50 lbs (22.7 kg)

FIRE RATINGS

Underwriters Laboratory International UL ER #8477-01. See technical data sheet for complete UL and fire assembly information.

PRO TIP

Maxxon Commercial Level EZ can be poured over primed, non-water soluble adhesive residue that is solidly bonded to the subfloor.

Can be a part of a Maxxon wear surface system. Contact Maxxon for details.



Maxxon Corporation

920 Hamel Road PO Box 253
Hamel, Minnesota 55340
800-238-8461

maxxon.com

info@maxxon.com

@Maxxon.Corporation

maxxon-corporation