

PRODUCT CODE: 13015
JUNE 2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Maxxon® Commercial Unglued

Trade Name: Unglued Glue Remover

Product Form: Mixture

Recommended uses: Pressure Sensitive Adhesive (PSA) & Flooring Glue and Matic Remover

Restrictions on uses:None identified

Supplier: Maxxon Corporation, 920 Hamel Road • PO Box 253 • Hamel, MN 55340

Company Telephone/Fax: (763) 478-9600 / (763) 478-2431

Emergency Telephone Number: (613) 996-6666 (CANUTEC)

2. HAZARDS IDENTIFICATION

GHS classification

Eye Irritation 2A

Hazard pictograms (GHS-US)



Signal word (GHS-US) Warning

Hazard statements (GHS-US) Wash hands, forearms and face thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EYE IRRITATION PERSISTS: Get medical

advice/attention.

Other hazards: No additional information available

Unknown acute toxicity: Not applicable



PRODUCT CODE: 13015

JUNE 2022

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances: Not Applicable

NAME	PRODUCT IDENTIFIER	%
Benzyl alcohol	(CAS-No.) 100-51-6	15 – 40

^{**}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

4. FIRST AID MEASURES

Description of first aid measures

First-aid

measures after inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Get medical attention if you feel unwell.

First-aid

measures after skin contact: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention

if irritation persists.

First-aid

measures after eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

First-aid

measures after ingestion: IF SWALLOWED: Do NOT induce vomiting without medical advice. Get medical

advice if you feel unwell. Never give anything by mouth to an unconscious

person.

Most important symptoms and effects, both acute and delayed

Symptoms/effects

after inhalation: May cause irritation to the respiratory tract.

Symptoms/effects

after skin contact: May cause skin irritation. Repeated exposure may cause skin dryness or

cracking.

Symptoms/effects

after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain,

excess blinking and tear production, with marked redness and swelling of the

conjunctiva.

Symptoms/effects

after ingestion: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting

and diarrhea.



PRODUCT CODE: 13015
JUNE 2022

4. FIRST AID MEASURES Continued

Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed: In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

5. FIRE FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water. Dry chemical. Foam. Carbon dioxide (CO2). Alcohol-resistant foam.

Unsuitable extinguishing media: Do not use water jet.

Special hazards arising from the

substance or mixture

Fire hazard: Products of combustion may include, and are not limited to: oxides of carbon.

Magnesium oxide. Silicon dioxide.

Advice for firefighters

Firefighting instructions: Exercise caution when fighting any chemical fire.

Protection during firefighting: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and

respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General measures: Use personal protection recommended in Section 8. Isolate the hazard area and

deny entry to unnecessary and unprotected personnel.

For non-emergency personnel: No additional information available
For emergency responders: No additional information available

Environmental precautions: Prevent entry to sewers and public waters.

Methods and material for containment and cleaning up

For containment: Absorb and/or contain spill with inert material (sand, vermiculite or other

appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up: Sweep or shovel spills into appropriate container for disposal. Provide

ventilation.

Reference to other sections: For further information refer to section 8: "Exposure controls/personal

protection"



PRODUCT CODE: 13015
JUNE 2022

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/

spray. Do not swallow. Handle and open container with care. When using do not

eat, drink or smoke.

Hygiene measures: Wash contaminated clothing before reuse. Wash hands, forearms and face

thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage area: Keep out of the reach of children. Keep container tightly closed. Store in a dry,

cool and well-ventilated place.

Incompatible materials: Refer to section 10 on incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Glue Remover:

ACGIH TWA (mg/m³):

10 mg/m³ (inhalable particulate matter)

ACGIH chemical category:

Not Classifiable as a Human Carcinogen

Benzyl alcohol (100-51-6):

No additional information available

Individual protection measures/ Personal protective equipment

Appropriate engineering controls: Ensure good ventilation of the work station. Provide readily accessible eye wash

stations.

Hand protection: Nitrile (chemical resistant) gloves are recommended and should be used at all

times when using this product.

Eye protection: Properly fitted safety glasses or splash goggles are recommended and should

be used when using this product. A face shield can also be used.

Skin and body protection: Wear suitable protective clothing. Such as coveralls or long sleeves.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has

assessed the work environments.

Environmental exposure controls: Avoid release to the environment.

Other information: Handle in accordance with good industrial hygiene and safety procedures. Do

not eat, drink or smoke when using this product.



PRODUCT CODE: 13015

JUNE 2022

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Paste

ColourLight BrownOdourAromatic

Odour thresholdNo data availablepHNot applicableMelting point-14 deg C/ 5 deg FFreezing point-15 deg C/ 5 deg FBoiling point>205°C (>401° F)Flash point>98.9°C (> 210°F)

Relative evaporation rate

(butylacetate=1)No data availableFlammability (solid, gas)Not flammableVapour pressureNo data availableRelative vapour density at 20 °CNo data availableRelative densityNo data available

Solubility Slight

Partition coefficient

n-octanol/waterNo data availableAuto-ignition temperatureNot applicableDecomposition temperatureNo data available

Viscosity, kinematic Paste

Viscosity, dynamic

Explosive limits

Not applicable

Explosive properties

Not applicable

Oxidising properties

Not applicable

Other information: No additional information available



PRODUCT CODE: 13015
JUNE 2022

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reactions known under normal conditions of use.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

Conditions to avoid: Heat. Incompatible materials.

Incompatible materials: Strong oxidizers, strong acids, strong bases.

Hazardous decomposition

products: May include, and are not limited to: oxides of carbon. Magnesium oxide.

Silicon dioxide

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral: Not classified

Dermal Not classified

Inhalation Not classified

ATE CA (oral): 1230 mg/kg bodyweight

ATE CA (vapours): 11 mg/4h

BENZYL ALCOHOL (100-51-6)		
LD50 oral rat	1,230 mg/kg	
LD50 dermal rabbit	2 g/kg	
LC50 inhalation rat	>4178mg/m3 (exposure time 4h)	
ATE CA (dermal)	2000 mg/kg bodyweight	
ATE CA (gases)	4500 ppmv/4h	
ATE CA (dust, mist)	1.5 mg/l/4h	

Skin corrosion/irritation: Not classified; pH:4-5

Serious eye damage/irritation: Causes serious eye irritation; pH: 4–5

Respiratory or skin sensitisation:Not classifiedGerm cell mutagenicity:Not classifiedCarcinogenicity:Not classifiedReproductive toxicity:Not classifiedSTOT-single exposure:Not classifiedSTOT-repeated exposure:Not classifiedAspiration hazard:Not classified

Symptoms/effects

after inhalation: May cause irritation to the respiratory tract.

Symptoms/effects

after skin contact: May cause skin irritation. Repeated exposure may cause skin dryness or

cracking.

BEB LD50

LD50



PRODUCT CODE: 13015
JUNE 2022

11. TOXICOLOGICAL INFORMATION Continued

Symptoms/effects

after eye contact: Causes serious eye irritation. Symptoms may include discomfort or pain,

excess blinking and tear production, with marked redness and swelling of the

conjunctiva.

Symptoms/effects

after ingestion: May be harmful if swallowed. May cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Other information: Likely routes of exposure: ingestion, inhalation, skin and eye.

12. ECOLOGICAL INFORMATION

Ecology: May cause long-term adverse effects in the aquatic environment.

BENZYL ALCOHOL (100-51-6)		
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Crustacea 1	23 mg/l (Exposure time: 48 h - Species: water flea)	
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
NOEC (chronic)	51 mg/l Test organisms (species): Daphnia magna Duration : '21 d'	
NOEC chronic fish	48,897 mg/l Test organism (species): other: Duration: '30 d'	

PERSISTENCE AND DEGRADABILITY

GLUE REMOVER	
Persistence and degradability	Not established

BIOACCUMULATIVE POTENTIAL

GLUE REMOVER	
Bioaccumulative potential	Not established.

BENZYL ALCOHOL (100-51-6)	
Partition coefficient n-octanol/water	1.1

BENZENESULFONIC ACID, C10-16-ALKYL DERIVATIVES (68584-22-5)	
Partition coefficient n-octanol/water	2 (at 23 °C)

Mobility in soil: No additional information available

Other adverse effects: No other effects known.



PRODUCT CODE: 13015
JUNE 2022

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Product/Packaging

disposal recommendations The generation of waste should be avoided or minimized whenever possible.

Dispose of product in accordance with all local, regional, national and/ or international regulations. Empty containers or liners may retain some product

residue. Recycle empty containers where permitted.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG /

IMDG/IATA: Not regulated

15. REGULATORY INFORMATION

Federal regulations: All components of this product are listed, or excluded from listing, on the

United States Environmental Protection Agency Toxic Substances Control Act

(TSCA) inventory.

All components of this product are listed, or excluded from listing, on the

Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances

List) inventories.

International regulations: No additional information available



PRODUCT CODE: 13015

JUNE 2022

16. OTHER INFORMATION

Product List: Maxxon Commercial Primer

Issue Date: June 2022

Version: 01

Revision Date: March 2023

Prepared by: Maxxon Corporation

HMIS® ratings:

Health: 2A
Flammability: 0
Reactivity: 2A

NFPA ratings:

Health: 0
Flammability: 0
Reactivity: 0

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe *=Chronic

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

According to the Hazard Communication Standard (CFR29 1910. 1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date: 3/17/2023 Other information: None

Prepared by: Nexreg Compliance Inc. www.Nexreg.com

Full Text of H - statements

Eye Irrit. 2A: Serious eye damage/eye irritation, Category 2A