

**MAXXON®**

COMMERCIAL

**Unglued**

ADHESIVE REMOVER



## REMOVE ADHESIVES WITH EASE

Maxxon® Commercial Unglued Adhesive Remover streamlines the removal of pressure sensitive adhesives (PSAs), flooring mastics, glues, and other water-based and non-water-based adhesives. It's the smart replacement for time-consuming mechanical or abrasive methods.

- Effective in removing PSAs, flooring mastics, glues, and adhesives
- Fast-acting (2–4 hour typical dwell time)
- Non-toxic and non-caustic
- Fully biodegradable
- Low odor: no forced ventilation required

### WHERE TO USE

#### *Application*

Commercial and residential renovation.

#### *Subfloor*

Interior concrete, wood.



See Unglued in action!

**BENEATH IT ALL, MAXXON DELIVERS.™**

**EASY ADHESIVE REMOVAL  
 WITHOUT HARMFUL RESIDUE.**

Maxxon<sup>®</sup> Commercial Unglued removes adhesives by swelling polymers and weakening adhesive properties. After a two- to four-hour dwell time, it's easily scraped away from the substrate and cleaned with water and a black pad, leaving no harmful residues in the substrate. Simply roll it on and let it work.

Non-toxic, fully biodegradable and with zero VOCs, Maxxon<sup>®</sup> Commercial Unglued turns even the stickiest subfloor situation into a clean slate for proper curing of fresh adhesives

**PRODUCT INFORMATION**

VOCs	0 g/L
Color	Light Brown
Installation Temperature	54–95 °F (12–35 °C)
Dwell Time	Typically 2–4 hours
Coverage	80–100 ft <sup>2</sup> /gal (7.4–9.3 m <sup>2</sup> /L); 320–400 ft <sup>2</sup> /pail (29.7–37.2 m <sup>2</sup> /L)
Shelf Life	2 years unopened 1 year after opening (remix before re-use)



**INSTALLATION & LIMITATIONS**

See technical data sheet available at Maxxon.com for limitations and complete installation instructions.

**PACKAGING**

4 gal. (15.1 L) Unglued in a 5 gal. pail

**PRO TIP**

If crews roll on Unglued first thing in the morning, they can move to other tasks and return in the afternoon to scrape it off.

**Maxxon Corporation**  
 920 Hamel Road PO Box 253  
 Hamel, Minnesota 55340  
 800-238-8461  
[maxxon.com](http://maxxon.com)  
[info@maxxon.com](mailto:info@maxxon.com)

@Maxxon.Corporation  
 maxxon-corporation