

PRODUCT DESCRIPTION

Maxxon® Reinforcement (MR) is a reinforcement mesh used in conjunction with Maxxon® Underlayments for crack suppression. MR is a PVC coated, non-woven, fiberglass grid.

WHERE TO USE

Application

Systems with above average deflection.

Subfloor

All interior subfloors.

FEATURES & BENEFITS

- Excellent durability
- Light - easy to handle
- No memory (lays flat)
- Dimensionally stable in hot weather; not brittle in cold
- Long rolls reduce installation cost (compared to conventional galvanized metal lath)
- Can be used over Maxxon® Acousti-Mat® and in Maxxon Underlayment to reduce thickness of underlayment

PRODUCT INFORMATION

Thickness	0.015" (.38 mm)
Roll Width	45.63" (115.9 cm)
Roll Length	450 ft (137.1 m)
Roll Diameter	9.5" (24.1 cm)
Roll Weight	70 lbs (31.8 kg)
Roll Yield	1,711 ft ² (158.9 m ²)

GLASS CONSTRUCTION (VISUAL/INCH)

GRID PROPERTY	VALUE	TEST METHOD
Machine Direction	1.9	ASTM D-3775
Cross Machine	2.0	ASTM D-3775

TENSILE (LB) (2 ENDS)

GRID PROPERTY	VALUE	TEST METHOD
Machine Direction	150	ASTM D-5035
Cross Machine	180	ASTM D-5035
Width (inches)	46.5	ASTM D-3774

Values listed above are nominal and are only to be used as guidelines.

INSTALLATION

Surface Preparation

All subfloors must be structurally sound, solid, free of dirt, mud and dust. Over oil, grease and other surface contaminants, MR must be mechanically attached. All subfloors must be dry and a minimum of 50 °F (10 °C).

Methods of Attachment

Wood Frame: Loose lay MR wall to wall overlapping 1–2 inches or mechanically fasten MR to the wood subfloor with staples approximately 2–4 feet o.c. Do not pull taught. The Maxxon Reinforcement should float off the subfloor but not be visible at the surface. Top with a minimum of 3/4" (19 mm) approved Maxxon Underlayment.

Concrete/Precast Concrete: Loose lay MR wall to wall overlapping 1–2 inches, then MR can be spot glued to concrete subfloor with contact glue, Maxxon® Acousti-Top® Adhesive, or equal. Top with a minimum 1/2" (13 mm) approved Maxxon Underlayment.

Maxxon Acousti-Mats: Loose lay MR perpendicular to the direction of the Acousti-Mat wall to wall overlapping 1-2 inches. Contact adhesive can be used where necessary to spot glue the MR to the Acousti-Mat.

Product	Topping Minimum
Acousti-Mat 1/4	3/4" (19 mm)
Acousti-Mat 1/4 Premium	3/4" (19 mm)
Acousti-Mat 3/8	3/4" (19 mm)
Acousti-Mat 3/8 Premium	3/4" (19 mm)
Acousti-Mat 3/4	1-1/2" (38 mm)
Acousti-Mat 3/4 Premium	1-1/2" (38 mm)
Double Mat System	2" (51 mm)

WARRANTY AND TECH SERVICES

Contact Maxxon before your project for complete warranty information. Technical performance verification and service is available through Maxxon Corporation or Maxxon Regional Representatives throughout North America.

JOB NAME: _____

DATE: _____

APPLICATOR: _____

Maxxon Corporation assumes no responsibility or liability for any errors or omissions in the content of this document. The information contained is subject to change without notice. Follow local and state regulations and use appropriate safety precautions and measures when installing Maxxon products. See related product literature at Maxxon.com or contact Maxxon Corporation for more information prior to installation.

©2023 Maxxon Corporation. All Rights Reserved. Maxxon and associated logos are registered trademarks of Maxxon Corporation, Hamel, MN, USA. Other trademarks, registered trademarks, product names or logos displayed are the property of their respective owners.



Maxxon Corporation

920 Hamel Road PO Box 253
 Hamel, Minnesota 55340
 800-356-7887
maxxon.com

info@maxxon.com

@Maxxon.Corporation

maxxon-corporation