



MAXXON

INNOVATIVE MOISTURE MITIGATION SOLUTIONS

Maxxon's new line of commercial products provide innovative, cost-effective solutions for moisture and contamination control with even the most challenging subfloors and concrete slabs. We help you work smarter, not harder. And we are there to help you with the expertise to get the job done right. Every time.

STEP 1 PREPARE & PREP SURFACE



MAXXON® **COMMERCIAL** **Profile**

PRODUCT DESCRIPTION

Concrete cleaner and profiler designed to purge contaminants from concrete surface, while creating a CSP of 1-4 with no shotblasting. Biodegradable, clean with water.

INFO

Dwell Time: 15 min for surface cleaning (approx)
2 hours to CSP 2
Coverage: 225-250 ft²/gal or 900-1,000 ft²
Packaging: 4 gal bucket



MAXXON® **COMMERCIAL** **Unglued**

PRODUCT DESCRIPTION

Adhesive remover effective in the removal of pressure sensitive adhesives (PSAs) and other flooring mastics, glues and adhesives (water-based and non-water-based).

INFO

Dwell Time: Typically 2-4 hours
Coverage: 80-100 ft² /gal
One kit covers 320-400 ft²
Packaging: 4 gal kit

STEP 2 APPLY MOISTURE MITIGATION



MAXXON[®] COMMERCIAL MVP One

PRODUCT DESCRIPTION

Ready-to-use, single-component moisture barrier and primer. Two-coat application dries in 60 minutes per coat. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

INFO

Packaging: 5 gal bucket
Total Coverage: 1,250 ft²
for 2-coat system



MAXXON[®] COMMERCIAL MVP Two-Part Epoxy

PRODUCT DESCRIPTION

Two-part epoxy moisture barrier. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

INFO

Total Coverage: 312 ft²
Packaging: 2.5 gal kit



MAXXON[®] COMMERCIAL MVP SMART Primer

PRODUCT DESCRIPTION

A spray-applied curing agent and moisture barrier for concrete. Used as part of the Maxxon SMART System to expedite new concrete construction.

INFO

Dry Time: 30 min – 2 hours
Coverage: 175 ft²/gal
Packaging: 4 gal bucket

CONTAINMENT AND MOISTURE CONTROL



MAXXON[®] COMMERCIAL Isolate

PRODUCT DESCRIPTION

A two-part, water-based epoxy that isolates chemically-abated slabs, asbestos-containing material, and other contaminants in concrete slabs. Also prevents the migration of moisture vapor from adversely affecting floor coverings.

INFO

Dry Time: 4-6 hours
Coverage: 150 ft²/gal or 600 ft²/kit
Packaging: 4 gal (15.1 L) bucket

STEP 3 FINISH WITH LEVELING & PRIMING



MAXXON[®] COMMERCIAL Level EZ™

PRODUCT DESCRIPTION

A low-prep, hydraulic cement-based underlayment that provides a strong, durable, smooth surface for floor coverings. Can be poured or pumped. UL Fire Rated.

INFO

Installation Depth: Featheredge to 2"
Compressive Strength: Minimum 5,000 psi
Coverage at 1/4": Approximately 24 ft²*
Packaging: 50 lb bag
*Depends on water demand used and slab condition.



MAXXON[®] COMMERCIAL EZ Crete™

PRODUCT DESCRIPTION

A low-prep, cost-effective cementitious underlayment for leveling, smoothing and repairing interior gypsum and concrete subfloors. UL Fire Rated.

INFO

Installation Depth: 3/8" to 3"
Compressive Strength: Minimum 4,000 psi
Bag Size: 50 lb
Coverage at 3/8": 16 ft²



MAXXON[®] COMMERCIAL Multi-Use Acrylic

PRODUCT DESCRIPTION

Primes concrete, gypsum, and wood subfloor before application of a Maxxon underlayment.

INFO

Packaging: 5 gal bucket
Total Coverage: Up to 2,100 ft²
Varies by application

Contact your Maxxon Commercial Sales Manager for more information.